



1/1.8" F2.8 C Mount				Working distance	Optical Magnification	1/1.8" Field of View(mm)	
Focal Length		f=50mm		mm		H	V
F/NO		F=2.8-22		1200	0.043X	164.2	112.6
Image Size		1/1.8"(7.2x5.3mm)	1/2.5"(5.76x4.32mm)	1/3"(4.8x3.6mm)	1100	0.047X	150.0
Angle FOV	H	8.2	6.6	5.5	1000	0.052X	135.8
	V	6.1	4.9	4.1	950	0.055X	128.7
	D	10.2	8.2	6.9	900	0.059X	121.6
Object Dimension at WD.300mm	H	36.1	29.4	24.5	850	0.062X	114.5
	V	27.1	22.1	18.4	800	0.066X	107.4
	D	45	36.1	30.6	750	0.071X	100.3
Distortion (TV)		<0.05%		700	0.076X	93.2	69.6
Focus distance(min)		300mm		650	0.083X	86.1	64.3
Flange back		17.526mm in air		600	0.090X	78.9	59
Back focus		17.4-27.1mm in air		550	0.099X	71.9	53.7
Filter screw size		无		500	0.110X	64.8	48.4
Front/Rear Effective Dia		Front ϕ 17.4mm Rear ϕ 8mm		450	0.124X	57.6	43.1
Mount		C-Mount		400	0.141X	50.5	37.7
Temperature Range		-10~+50°C		350	0.164X	43.4	32.4
Storage Temperature Range		-20~+60°C		300	0.196X	36.1	27.1

				TOLERANCE: LINEARITY TOLERANCES ± 0.05 ANGULAR TOLERANCES ARE $\pm 30'$ DRAFT ANGLES AREA $\pm 0.5^\circ$ /SIDE		三角法		材料(环保)		单位	比例	
						---		mm		2:1		
				设计	朱周德	2016-09-12	名称	RZ5001C5规格图				
				校对				页码				
				审核				1/1				
				标记	处数	更改文件号	担当	变更日期	批准	版本		
								V0				